

PVDF (Polyvinylidene Fluoride) is a highly non-reactive and pure thermoplastic fluoropolymer used in a variety of applications where the highest purity, strength, and resistance to solvents, acids, bases, and heat are required. PVDF pre-painted steel is best suited for high-end applications such as commercial or residential roofing, pre-engineered buildings, architectural wall panels, facades, and other applications where durability and long-lasting performance are required.




REGAL WHITE
SRI: 78



PARCHMENT
SRI: 58



SIERRA TAN
SRI: 58



CHAMPAGNE METALLIC
SRI: 49



MOCHA
SRI: 35




WEATHERED COPPER
SRI: 27



BRONZE
SRI: 25



DARK BRONZE
SRI: 27



COPPER PENNY
SRI: 42



TERRA COTTA
SRI: 42



COLONIAL RED
SRI: 34



RETRO RED
SRI: 25



HEMLOCK GREEN
SRI: 37



FOREST GREEN
SRI: 30



HARTFORD GREEN
SRI: 27



BLACK
SRI: 24




SILVER METALLIC
SRI: 58



OXFORD BLUE
SRI: 25



REGAL BLUE
SRI: 25



WEATHERED ZINC
SRI: 40




OLD TOWN GREY
SRI: 42



OLD ZINC GREY
SRI: 40



SLATE GREY
SRI: 30



ZINC GREY
SRI: 37

The Solar Reflectance Index (SRI) is a measure of the roof's ability to reject solar heat, as shown by a small temperature rise. SRI is a gauge from 0-100, with 0 being most likely to absorb and radiate heat (such as a tar roof) and 100 being the most reflective (least likely to get hot)