



AnchorDeck™ is a next generation synthetic roofing underlayment for sloped roof applications.

AnchorDeck™ coating technology allows underlayment to be anchored to the deck prior to applying fasteners. Innovative high-traction walking surface, excellent durability and many other unique performance features make AnchorDeck™ the smart choice for today's roofing professionals.

AnchorDeck™ is designed for use under asphalt shingles, metal in residential applications, synthetic shingles and primed cedar shakes. AnchorDeck™ meets all the code requirements including ASTM D226, ASTM D4869 and AC 188 as required by ICC-ES. AnchorDeck™ not only protects your roof deck, it helps protect roofers as well.

Ask for it at your nearest roofing distributor today.

NEXGEN™
SYNTHETICS

**ALL TEMP. ALL WEATHER
PERFORMANCE**



SNOW



STORMS



RAIN



HAIL



WIND



UV

- AnchorDeck™ has a unique coating technology which allows underlayment to be anchored to the deck prior to applying fasteners.
- All temp. all weather performance; remains flexible and easy to install in freezing or extremely hot conditions (-40° to 212°F)
- *No stretching around fasteners & no blow-offs!
- Innovative high traction walking surface
- Meets ASTM D226 Types I & II and D4869 Types II & IV
- Meets the performance requirements of CAN/CSA 123.3
- ICC-ES ESR-4055 | FBC Approved – FL21895
- Class A Fire Rating - ASTM E108
- Texas Department of Insurance Approved
- High Definition (HD) printing
- 90 Days UV Exposure
- 20 year warranty



20 Year
LIMITED WARRANTY

SEE REVERSE
FOR MORE!

**PRINT
YOUR LOGO[®]
HERE!**

www.YOURWEB.com

*Attract new customers
and increase awareness in
your local area!*



Sentry Building Innovations

1209 Orange Street, Wilmington,
New Castle, Delaware 19801

Customer Service: 1-843-735-1773

Test/Standard*

Tensile Strength ASTM D5034
Tear Strength ASTM D4533
Liquid Water Transmission ASTM D4869
Fire Rating ASTM E108
UV Exposure
Temperature Range

Typical Value

MD 95 lbs (43 kg) | CD 85 lbs (38.5 kg)
MD 18 lbs (8.16 kg) | CD 16 lbs (7.26 kg)
Pass
Class A
3 Months
-40° F - 212° F

Roll/Pallet Specs

Length per roll:	286' / 87 m
Width per roll:	42" / 1.1 m
Weight per roll:	23 lbs / 10.4 kg
Roll size:	10 sq / 93 m ²
Rolls per pallet/truck:	49 / 1,960
Pallet weight:	1,177 lbs / 534 kg

*Test data is based on average taken over several production runs and should not be considered or interpreted as minimum or maximum values. Values are typical data and not limiting specifications. All values $\pm 10\%$. This product is manufactured in accordance with national standards which allow for non-critical variances in weights and measures. RN-AD-FLR R1 18JAN2019

†When correctly installed as per AnchorDeck™ installation instructions. All Roofnado™ product installation instructions are available to download or view from our website: www.roofnado.com



ALL-WEATHER PROTECTION



NEXGEN™
SYNTHETICS

Roofnado™ AnchorDeck™ PSU

AnchorDeck™ PSU is a self-adhered (high temp) roofing underlayment for sloped roof applications. AnchorDeck™ PSU provides unmatched protection from ice dams, snow, storms, hail and wind-driven water. AnchorDeck™ PSU features a mechanical slip-resistant walking surface which provides superior steep-slope walkability.

To speed your projects up even more, AnchorDeck™ PSU has a split-release liner which helps increase productivity with faster and easier installs than single sheet liners. And for added confidence, AnchorDeck™ PSU's rubberized adhesion technology has an excellent combination of strong deck grip in low temperatures and high temperature flow resistance.

AnchorDeck™ PSU is designed for use under asphalt shingles, residential metal, concrete tiles, shakes, synthetic shingles and primed cedar shakes. AnchorDeck™ PSU meets all building code requirements including ASTM D226, ASTM D4869 and AC 48.

Ask for it at your nearest roofing distributor today.

Test/Standard*

Typical Value

Nominal thickness	40 mils
Weight per square	18.75 lbs
Permeability E96	0.027 Perms
Nail Sealability ASTM D1970	Pass
Tensile Strength ASTM D5034	MD 95 lbs (43 kg) CD 85 lbs (38.5 kg)
Tear Strength ASTM D4533	MD 25 lbs (11.3 kg) CD 20 lbs (9 kg)
Adhesion to Plywood ASTM D903	2.4 lbs/inch
Liquid Water Transmission ASTM D4869	Pass
Fire Rating ASTM E108	Class A
UV Exposure	90 Days

Roll/Pallet Specs

Length per roll:	67' / 20.4 m
Width per roll:	36" / .91 m
Weight per roll:	37.5 lbs / 17 kg
Roll size:	2 sq / 20 m ²
Rolls per pallet:	25
Pallet weight:	987.5 lbs / 448 kg

*Test data is based on average taken over several production runs and should not be considered or interpreted as minimum or maximum values. Values are typical data and not limiting specifications. All values ± 10 %. This product is manufactured in accordance with national standards which allow for non-critical variances in weights and measures.
RN AD PSU SS R2 DEC20

Features & Benefits

- Mechanical slip resistant walking surface which provides superior steep slope walkability for roofers
- Split release liner for faster & easier installs
- Rubberized adhesion technology for stronger deck grip
- Temperature range – 40° F to 240° F
- Meets the performance requirements of CAN/CSA A220.1
- Meets and exceeds ASTM D1970
- Low temperature flexibility – AC 48 PASS
- Thermal Stability – 190° F
- 20 Year Warranty
- 90 days UV exposure



Steep slope confidence

Nexgen™ mechanical and chemical slip-resistant technologies for unmatched walkability you can trust – every time.

Switch to Roofnado™ and start saving on labor, time & money.
Contact us today!
www.roofnado.ca

