



## Butyl Overlap Tap

REFERENCE	SIZE	UNIT	
GSMB10A16797	3/32" x 1/2"	ROLL	40'
GSMB10A11397A	3/32" x 1"	ROLL	40'

Combines the adhesive power of tape with the sealing power of caulk and other sealing products. Ideal for sealing and waterproofing



## Polycarbonate Snow Guard

REFERENCE	SIZE	UNIT
Z15 (Colour)	1.5" x 5" x 2.325"	EACH

Prevent snow slides with guards that hold snow evenly allowing it to melt gradually and drain off into gutters & leaders. Manufactured using a polycarbonate stronger than bullet-proof glass. 8 Colours in Stock.



## Neutral Cure Adhesive Sealant (Clear)

REFERENCE	SIZE	UNIT
SEALANTNC	300ml	TUBE

Used for installing polycarbonate snow guards. A high quality, single-component, 100% silicone sealant which provides superior adhesion to materials and surfaces where general purpose silicones fail.



## SB-190 Everseal Adhesive Sealant

REFERENCE	SIZE	UNIT
SEALANTSB	300 mL	TUBE

Used for installing polycarbonate snow guards. Versatile, high-strength, one-part adhesive sealant. Superb 2,000 PSI tensile strength with excellent impact resistance. Water & weather-proof. **Minimum Install Temperature 10C**



## Steel-Pro® Ferrous Metal Blade

REFERENCE	SIZE	UNIT
PRF18548BWK	7¼"x.079"x48Tx.625"	EACH



## Weathertight Sealant

REFERENCE	COLOUR	SIZE	UNIT
WT61111	CLEAR	300 mL	TUBE

Waterproof seal against water, wind, dust, dirt, or any other infiltration. Adheres to almost any common building substrate or material.



## 18ga Gutter Hanger

REFERENCE	SIZE	UNIT
GH5G	5"	EACH
GH6G	6"	EACH



## Aluminum Downspout Pop-In

REFERENCE	SIZE	UNIT
BMOT6650990	3.375"	EACH



## Roofnado Anchordeck PSU

REFERENCE	SIZE	UNIT
SOP00929	36" x 67'	ROLL


Peel & Stick Synthetic Roof Underlayment for metal panels and other roofing materials. Premium protection from Ice Dams, Snow, Storms, Hail & Wind-Driven Water. Mechanical slip resistant walking surface which provides superior steep slope walkability for roofers. **For Slopes 2/12 & Greater**



## Roofnado AnchorDeck

REFERENCE	SIZE	UNIT
TYROOF	42" x 286'	ROLL

Mechanically Attached Synthetic Roof Underlayment for metal panels and other roofing materials. AnchorDeck™ coating technology which allows underlayment to be anchored to the deck prior to applying fasteners. All temp. all weather performance; Innovative high traction surface provides excellent walkability



## RESISTO LASTOBOND PRO HT-N

REFERENCE	SIZE	UNIT
SOP10107	36" x 65'	ROLL

1 mm self-adhesive waterproofing membrane Roof Underlayment made of elastomeric SBS bitumen and a trilaminate woven polyethylene surface. The underface is composed of a silicone film easily detachable in two parts. The membrane is ideal under all types of cladding. **For Slopes 1/12 or Greater**



## Insulated Door

REFERENCE	SIZE*	UNIT
3068SF	38 x 81-3/16"	EACH
4068SF	49-7/8" x 81-3/16"	EACH

\*note: Exact door size listed. Allow 1/4" to 1/2" per side for Rough Opening